



EFFER 80 D

TECHNICAL SPECIFICATION

EFFER 80 D

TECHNICAL DATA	80 D B-1	80 D B-2	80 D B-3	80 D E-4
Max. lifting capacity (ft-lbs)	54 579	52 367	50 154	47 941
Outreach, hydraulic extensions (ft)	17' 8.6"	23' 7.5"	30' 2.2"	38' 0.7"
Outreach, manual extensions (ft)	23' 7.5"	30' 2.2"	37' 0.9"	-
Outreach / lifting capacity (ft-lbs)	8' 6.4" - 6283.2 12' 5.6" - 4365.2 17' 8.6" - 3086.5 - -	9' 2.2" - 5732.0 12' 5.6" - 4188.8 17' 8.6" - 2910.1 23' 7.5" - 2160.5 -	9' 6.2" - 5291.1 12' 5.6" - 4012.4 17' 8.6" - 2733.7 23' 11.4" - 1940.1 30' 2.2" - 1543.2	7' 2.6" - 6393.4 13' 5.4" - 3571.5 18' 8.4" - 2381.0 24' 11.2" - 1675.5 31' 2.0" - 1278.7 38' 0.7" - 1036.2
Slewing angle (°)	190 - 406	190 - 406	190 - 406	190 - 406
Height in folded position (in)	6' 2.8"	6' 2.8"	6' 2.8"	6' 2.8" - 6' 3.4"
Width in folded position (in)	6' 9.1" - 6' 11.1"	7' 0.3" - 7' 2.2"	7' 2.2"	7' 8.3"
Installation space needed (in)	2' 5.5" - 2' 7.3"	2' 5.5" - 2' 7.3"	2' 5.5" - 2' 9.7"	2' 5.5" - 2' 8.7"
Weight, "standard" crane without stabilizers (lbs)	1929	2138,5	2336,9	2513,3
Weight, stabilizer equipment (lbs)	668	668	668	668
Weight, jib (lbs)	-	-	-	-


Features

- D-Drive remote control system
- VSL: Variable Stability Limit (Optional)
- · LSS-V: Load Stability System
- 1 Year warranty All inclusive
- · 3 Year warranty Structural

- · SAF: Semi Automatic Folding
- HiConnect
- nDurance[™] nano technology coating







Hiab is a leading provider of smart and sustainable load handling solutions. We are committed to delivering the best customer experience every day with the most engaged people and partners. Hiab's premium equipment includes HIAB, EFFER and ARGOS loader cranes, MOFFETT and PRINCETON truck mounted forklifts, LOGLIFT forestry cranes, JONSERED recycling cranes, MULTILIFT skiploaders and hooklifts, GALFAB roll-off cable hoists, and tail lifts under the ZEPRO, DEL and WALTCO brands. As the industry pioneer, Hiab continues to make load handling smarter, safer and more sustainable to build a better tomorrow.



Hiab USA, Inc. 12233 Williams Rd Perrysburg, 43551 OH USA tel. +419 482 6000